ENPS-MF1

1 Port USB Multifunctional Print Server

Product Descriptions:

A. Interface:

- **USB:** One USB 2.0 High speed compliant port, supporting 1.5 Mbps (low speed), 12 Mbps (full speed) and 480 Mbps (high speed) data transmission rate. This port automatically detects the make and model of the printer attached to it.
- **LAN:** Compliant with IEEE 802.3 / 802.2u standard, 10/100 Mbps auto sensing, RJ 45 (UTP) connector.

** This product does not support use of USB hubs for daisy-chained connection, USB-to-Parallel connectors, or USB cable extenders.*

B. Key Software Specifications:

Setup CD	Yes (Windows Setup CD-ROM)
Network Operating System Support	Windows® 2000/XP and Windows Vista™
Network Protocol Support*	UDP TCP/IP
DHCP (client) Support	Yes
Management	1. Web interface 2. Windows-based Setup Program 3. Configuration Utility
Firmware Upgradeable	1. Web interface 2. TFTP
MFP Support	Printing, Scan, Fax and Card reader

C. Hardware Specifications:

CPU	Embedded high-performance RISC-cored SoC processor
Flash	1MB
System Memory	2 MB SDRAM
USB Port	USB 2.0 standard compliant host controller
LAN Port	10/100 Mbps, auto-sensing
Reset Button	Yes (Reset / Load Factory Defaults)
Power Supply	100-240V input / 3.3V, 2A Output
Dimension	74 (Length) x 63 (Width) x 30 (Height) mm
Weight	57 g (device only)
EMI Certifications	CE / FCC Class B
Temperature	Operating 0 ~ 50°F; Storage -5 ~ 65°F
Humidity	Operating 0 ~ 70%; Storage 0 ~ 80%

The specification is subject to change without prior notice.